



	M330	M330G	M424G	M400BB	M510	M605
<b>Specifications</b>						
RF Output Power	25 W / 1 W	25 W / 1 W	25 W / 1 W	25 W / 1 W	25 W / 1 W	25 W / 1 W
AF Output Power	4.5 W	4.5 W	4 W	2 W	15 W	15 W
IP Rating	IPX7 (1 m depth/30 min)	IPX8 (1 m depth/60 min)	IPX7 (1 m depth/30 min)	IPX7 (1 m depth/30 min)	IP68 (1 m depth/60 min)	IPX8 (1 m depth/60 min)
Mil Spec Rating	NA	NA	NA	NA	810-C/D/E/F/G	810-C/D/E/F/G
<b>Features</b>						
NMEA 2000®	NA	NA	NA	NA	w/CT-M500	√
NMEA 0183®	√	√	√	√	√	√
DSC	√	√	√	√	√	√
AquaQuake™	√	√	√	√	√	√
Tag Scan/ Favorite Channel	√	√	√	√	√	√
Dual/Tri-watch	√	√	√	√	√	√
Priority Scan	√	√	√	√	√	√
RX Weather Channel	√	√	√	√	√	√
GPS Antenna	NA	Supplied External	Internal Only	NA	Optional, UX-241	GNSS Antenna Included
AIS (RX)	NA	NA	NA	NA	M510 Plus	M605 AIS
AIS (TX/RX)	MA-510TR	MA-510TR	MA-510TR	MA-510TR	MA-510TR	MA-510TR
Hailer/Foghorn	NA	NA	√	√ <sup>1</sup>	w/CT-M500	√
Active Noise Cancelling	NA	NA	√	√	√	√
Voice Scrambler	NA	NA	NA	NA	Optional	√
<b>Accessories</b>						
Removable Microphones	NA	NA	NA	NA	√	√
Rear Mic	NA	NA	NA	NA	HM-205RB**	HM-205RB**
Speaker Mic	HM-235B/SW	HM-235B/SW	HM-205B	NA	HM-205RB**	HM-205RB**
Commandmic™	NA	NA	HM-195GB/GW	HM-195B/SW	HM-195GB/GW	HM-195GB/GW
OPC Cables						
Command Mic	NA	NA	OPC-1540 OPC-1541	OPC-1540 OPC-1541	OPC-1540 OPC-1541	OPC-1540 OPC-1541
Rear Mic	NA	NA	NA	NA	OPC-1000	OPC-1000
Remote Head	NA	NA	NA	NA	NA	OPC-2384
Command Head	NA	NA	NA	NA	NA	RC-M600
iOS/Android™ APP	NA	NA	NA	NA	RS-M500	NA

### NOTES

1. PA function/Manual Foghorn function only.

\*Use one of the three combinations when setting up your M605:

M605 + three COMMANDMICS

M605 + two COMMANDMICS + one Command Head

M605 + two Command Heads + one COMMANDMIC

\*\*Rear mic requires OPC-1000

Any questions about these specifications, please contact Technical Support.

Call our Technical Team: Mon-Fri 4AM-5PM PST, (425) 454-8155 (Press #5)

Or: <https://icom.custhelp.com/>